



☄ DRYERS

TPM 100

infrared flash cure

- **functions:** drying
- **technical data:**
 - temperature: up to 350°C
 - timer: adjustable
 - heating area: 400 x 500 mm
 - total length: 660 mm
 - total width: 500 mm
 - total height: adjustable from 850 - 1200 mm
 - power supply: 230V / 2,0 kWh
 - net weight: 70 kg

recommended dryer for:
all TPM machines



low power consumption




DIN ISO9001



TPM 100 functions:



TPM 100 technical data:



TPM 110

drying tunnel

- **functions:** drying
- **technical data:**
 - transport speed: adjustable 0,5 - 5 m / min
 - temperature: 40° - 350°C
 - heating chamber 1: 1500 mm
 - band width: 600 mm
 - opening: 80 mm
 - total length: 2500 mm
 - total height: 1200 mm
 - total width: 900 mm
 - power supply: 400V / 4,5 kWh / MP 50 HZ
 - net weight: 200 kg

recommended dryer for:
all TPM machines



low power consumption




DIN ISO9001



TPM 110 functions:



TPM 110 technical data:



TPM 120

gas & infrared drying tunnel

- **functions:** drying
- **technical data:**
 - transport speed: adjustable 0,5 - 5 m / min
 - temperature: adjustable 40°C - 350°C
 - heating chamber 1: Infrared 600 mm
 - heating chamber 2: Gas 2700 mm
 - band width: 1800 mm
 - opening: 150 mm
 - total length: 6000 mm
 - total height: 1450 mm
 - total width: 2250 mm
 - power supply: 400V / 15,5 kWh / MP 50 HZ
 - net weight: 1800 kg

recommended dryer for:
TPM 746, 750



low power consumption



DIN ISO9001



TPM 120 functions:



TPM 120 technical data:

